



风机机座号 Fan frame size	转速 Speed (rpm)	流量 Volume (m ³ /h)	全压 Pressure (Pa)	噪声 Noise [dB(A)]	电压 Voltage (V)	频率 freq. (Hz)	电机机座号 Motor frame size	功率 Power (kW)	电流 Current (A)	重量 Weight (kg)	外形及安 装尺寸图 Page
十、LKPH 系列后向双进风带传动离心通风机											
LKPH Series Backward-curved-blade Double-inlet Belt-drive Centrifugal Fans											
LKPH450	1800	8300 ~ 11450	960 ~ 670	81	380	50	Y132S1-2	5.5	11.6	195	P103
	2000	9260 ~ 12730	1190 ~ 830	83	380	50	Y132S1-2	5.5	11.6	195	
	2200	10200 ~ 14000	1440 ~ 1000	85	380	50	Y132S2-2	7.5	15.4	210	
	2400	11100 ~ 15300	1710 ~ 1200	87	380	50	Y160M1-2	11	21.8	245	
	2600	12030 ~ 16550	2010 ~ 1410	89	380	50	Y160M2-2	15	29.4	255	
	2800	12960 ~ 17820	2330 ~ 1630	90	380	50	Y160L-2	18.5	35.5	275	
LKPH500	1800	11400 ~ 15700	1200 ~ 850	84	380	50	Y132M-4	7.5	15.4	240	P104
	1900	12030 ~ 16550	1340 ~ 940	85	380	50	Y160M-4	11	22.6	280	
	2000	12600 ~ 17400	1490 ~ 1040	87	380	50	Y160M1-2	11	22.6	280	
	2100	13300 ~ 18300	1640 ~ 1150	88	380	50	Y160M1-2	11	22.6	280	
	2200	13900 ~ 19100	1800 ~ 1260	89	380	50	Y160M2-2	15	29.4	285	
	2300	14600 ~ 20000	1960 ~ 1380	90	380	50	Y160M2-2	15	29.4	285	
	2400	15200 ~ 20900	2140 ~ 1500	91	380	50	Y160L-2	18.5	35.5	305	
LKPH560	1700	15150 ~ 20800	1330 ~ 930	86	380	50	Y160M-4	11	22.6	320	P105
	1800	16000 ~ 22000	1490 ~ 1050	87	380	50	Y160L-4	15	30	360	
	1900	16900 ~ 23280	1660 ~ 1160	88	380	50	Y160L-4	15	30	360	
	2000	17800 ~ 24500	1840 ~ 1290	89	380	50	Y160L-2	18.5	35.9	365	
	2100	18700 ~ 25700	2030 ~ 1420	90	380	50	Y180M-2	22	42.9	405	
	2200	19600 ~ 27000	2230 ~ 1560	91	380	50	Y200L1-2	30	56.9	445	
LKPH630	1500	19200 ~ 26400	1320 ~ 930	87	380	50	Y160L-4	15	30	420	P106
	1600	20500 ~ 28200	1500 ~ 1050	88	380	50	Y180M-4	18.5	35.9	455	
	1700	21760 ~ 29900	1700 ~ 1190	90	380	50	Y180L-4	22	42.9	470	
	1800	23000 ~ 31700	1900 ~ 1340	91	380	50	Y200L-4	30	56.8	505	
	1900	24300 ~ 33400	2120 ~ 1490	92	380	50	Y200L1-2	30	56.8	480	
	2000	25600 ~ 35200	2350 ~ 1650	93	380	50	Y200L2-2	37	70.4	515	



风机性能及技术参数 Performance parameters and technical data

风机机座号 Fan frame size	转速 Speed (rpm)	流量 Volume (m ³ /h)	全压 Pressure (Pa)	噪声 Noise [dB(A)]	电压 Voltage (V)	频率 freq. (Hz)	电机机座号 Motor frame size	功率 Power (kW)	电流 Current (A)	重量 Weight (kg)	外形及安 装尺寸图 Page
LKPH710	1300	23700 ~ 32600	1250 ~ 870	87	380	50	Y180M-4	18.5	35.9	565	P107
	1400	25500 ~ 35100	1440 ~ 1000	89	380	50	Y180L-4	22	42.9	580	
	1500	27300 ~ 37600	1660 ~ 1160	90	380	50	Y200L-4	30	56.8	635	
	1600	29160 ~ 40100	1890 ~ 1320	92	380	50	Y200L-4	30	56.8	635	
	1700	31000 ~ 42600	2130 ~ 1500	93	380	50	Y225S-4	37	70.4	690	
	1800	32800 ~ 45100	2390 ~ 1680	94	380	50	Y225M-4	45	84.2	720	
LKPH800	1000	25600 ~ 35200	950 ~ 670	85	380	50	Y160L-4	15	30	600	P108
	1100	28160 ~ 38700	1150 ~ 800	87	380	50	Y180M-4	18.5	35.9	630	
	1200	30700 ~ 42200	1370 ~ 960	89	380	50	Y180L-4	22	42.9	650	
	1300	33300 ~ 45760	1600 ~ 1130	91	380	50	Y200L-4	30	56.8	705	
	1400	35800 ~ 49300	1860 ~ 1300	93	380	50	Y225S-4	37	70.4	760	
	1500	38400 ~ 52800	2140 ~ 1500	94	380	50	Y225M-4	45	84.2	790	
LKPH900	1000	37100 ~ 51100	1200 ~ 840	90	380	50	Y200L-4	30	59.5	750	P109
	1100	40900 ~ 56200	1450 ~ 1020	92	380	50	Y225S-4	37	70.4	770	
	1200	44600 ~ 61300	1730 ~ 1210	93	380	50	Y225M-4	45	84.2	800	
	1300	48300 ~ 66400	2030 ~ 1420	95	380	50	Y250M-4	55	102.5	880	
	1400	52000 ~ 71500	2350 ~ 1650	97	380	50	Y280S-4	75	139.7	975	
LKPH1000	900	45400 ~ 625400	1180 ~ 830	90	380	50	Y200L-4	30	59.5	980	P110
	1000	50500 ~ 69400	1460 ~ 1020	93	380	50	Y225S-4	37	84.2	1000	
	1100	55500 ~ 76300	1760 ~ 1230	95	380	50	Y250M-4	55	102.5	1050	
	1200	60500 ~ 83200	2100 ~ 1480	97	380	50	Y280S-4	75	141.1	1155	
	1300	65600 ~ 90200	2460 ~ 1730	98	380	50	Y280M-4	90	168.6	1440	